

KL. 145, 245, 545, 1245, 335

Piedini scanalati con ago a destra per tracolle
Right needle cording feet for shoulder

MODELLO
(A)




A/P02 - 2,0 mm	A/P08 - 8,0 mm
A/P03 - 3,0 mm	A/P09 - 9,0 mm
A/P04 - 4,0 mm	A/P10 - 10,0 mm
A/P05 - 5,0 mm	A/P11 - 11,0 mm
A/P06 - 6,0 mm	A/P12 - 12,0 mm
A/P07 - 7,0 mm	



A/A02 - 2,0 mm	A/A08 - 8,0 mm
A/A03 - 3,0 mm	A/A09 - 9,0 mm
A/A04 - 4,0 mm	A/A10 - 10,0 mm
A/A05 - 5,0 mm	A/A11 - 11,0 mm
A/A06 - 6,0 mm	A/A12 - 12,0 mm
A/A07 - 7,0 mm	

Piedini scanalati con ago a destra per tracolle
Right needle cording feet for shoulders

MODELLO
(B)



B/P02 - 2,0 mm	B/P08 - 8,0 mm
B/P03 - 3,0 mm	B/P09 - 9,0 mm
B/P04 - 4,0 mm	B/P10 - 10,0 mm
B/P05 - 5,0 mm	B/P11 - 11,0 mm
B/P06 - 6,0 mm	B/P12 - 12,0 mm
B/P07 - 7,0 mm	



B/A02 - 2,0 mm	B/A08 - 8,0 mm
B/A03 - 3,0 mm	B/A09 - 9,0 mm
B/A04 - 4,0 mm	B/A10 - 10,0 mm
B/A05 - 5,0 mm	B/A11 - 11,0 mm
B/A06 - 6,0 mm	B/A12 - 12,0 mm
B/A07 - 7,0 mm	


Questi piedini sono utilizzabili anche per le macchine "NECCHI"

Thees feet are also used on "NECCHI machines"



Per la produzione di tracolle con anima interna


For production of shoulders with inside cord



KL. 145, 245, 545, 1245, 335

Piedini scanalati con ago a sinistra per orlature
Left needle piping feet

MODELLO
(C)




C/P02 - 2,0 mm	C/P08 - 8,0 mm
C/P03 - 3,0 mm	C/P09 - 9,0 mm
C/P04 - 4,0 mm	C/P10 - 10,0 mm
C/P05 - 5,0 mm	C/P11 - 11,0 mm
C/P06 - 6,0 mm	C/P12 - 12,0 mm
C/P07 - 7,0 mm	




C/A02 - 2,0 mm	C/A08 - 8,0 mm
C/A03 - 3,0 mm	C/A09 - 9,0 mm
C/A04 - 4,0 mm	C/A10 - 10,0 mm
C/A05 - 5,0 mm	C/A11 - 11,0 mm
C/A06 - 6,0 mm	C/A12 - 12,0 mm
C/A07 - 7,0 mm	

Piedini scanalati con ago a sinistra per orlature
Left needle piping feet

MODELLO
(D)



D/P02 - 2,0 mm	D/P08 - 8,0 mm
D/P03 - 3,0 mm	D/P09 - 9,0 mm
D/P04 - 4,0 mm	D/P10 - 10,0 mm
D/P05 - 5,0 mm	D/P11 - 11,0 mm
D/P06 - 6,0 mm	D/P12 - 12,0 mm
D/P07 - 7,0 mm	



D/A02 - 2,0 mm	D/A08 - 8,0 mm
D/A03 - 3,0 mm	D/A09 - 9,0 mm
D/A04 - 4,0 mm	D/A10 - 10,0 mm
D/A05 - 5,0 mm	D/A11 - 11,0 mm
D/A06 - 6,0 mm	D/A12 - 12,0 mm
D/A07 - 7,0 mm	

Questi piedini sono utilizzabili anche per le macchine "NECCHI"

Thees feet are also used on "NECCHI machines"



Per l'esecuzione di orlature con anima.

For cord hemming operations.

